Power Generation
G-Drive
N67

N67 TE3F
195 kWm @ 1500 rpm
Stage IIIA

POWER GENERATION

SPECIFICATIONS

Thermodynamic Cycle			Diesel 4 stroke
Arrangement			6L
Air Handling			TCA
Bore x Stroke	millimeters		104 x 132
Total Displacement	liters		6.7
Cooling System			liquid (water - paraflu 50%)
Direction of Rotation (viewed facing flywheel)			CCW
Speed governor			Electronic
Injection System			ECR
Flywheel housing		type	-
Flywheel size		inch	-
Oil and oil filter maintenance interval for replacement		hours	600
Specific fuel consumption at 1500 Stand-by		l/h (g/kWh)	- (-)
Specific fuel consumption at 1500 100% Prime Power		l/h (g/kWh)	45.5 (211)
Specific fuel consumption at 1500 80% Prime Power		l/h (g/kWh)	41.9 (243)
Specific fuel consumption at 1500 50% Prime Power		l/h (g/kWh)	29.9 (250)
Specific fuel consumption at 1800 Stand-by		l/h (g/kWh)	- (-)
Specific fuel consumption at 1800 100% Prime Power		l/h (g/kWh)	- (-)
Specific fuel consumption at 1800 80% Prime Power		l/h (g/kWh)	- (-)
Specific fuel consumption at 1800 50% Prime Power		l/h (g/kWh)	- (-)
ATB (without canopy) at 1500		°C	58
ATB (without canopy) at 1800		°C	-
Lube oil total system capacity including pipes, filters etc.		liter	~17
Electric system (isolated return)		Vcc	12
Starting batteries: recommended capacity		Ah	1 x 180 Ah
Discharge Current (EN50342)		A	800
Cold starting: without preheating		°C	-10
Cold starting: with preheating		°C	-25

WEIGHT AND DIMENSIONS

Dimensions	LxWxH (mm)	1713 x 796 x 1230
Dry Weight	Kg	630

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

PERFORMANCES

Rated Stand-by Power at 1500 rpm	kWm	195
Rated Prime Power at 1500 rpm	kWm	175
Rated Continuous at 1500 rpm		-
Rated Stand-by Power at 1800 rpm	kWm	-
Rated Prime Power at 1800 rpm	kWm	-
Rated Continuous at 1800 rpm		-

PRIME POWER: The prime power is the maximum power available with varying loads for an unlimited number of hours. The average power output during a 24h period of operation must not exceed 80% of the declared prime power between the prescribed maintenance intervals and at standard environmental conditions. A 10% overload is permissible for 1 hour every 12 hours of operation.

STAND-BY POWER: The stand-by power is the maximum power available for a period of 500 hours/year with a mean load factor of 90% of the declared stand-by power. No kind of overloads is permissible for this use.

CONTINUOUS POWER: Contact the FPT sales organization.

LEGEND

Arrangement
L (in line)
V (90° "V" configuration)

Air Handling
TCA (Turbocharged with aftercooler)
TC (Turbocharged)
NA (Naturally Aspirated)

Injection System
M (Mechanical)
ECR (Electronic Common Rail)
EUI (Electronic Unit Injector)
MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE

OPTIONAL EQUIPMENT

Upon specific request, engines can be supplied with the following accessories: - 24V electric system - Water pre-heater - Exhaust elbow with flexible bellow - Exhaus silencer (loose) - Instrument senders (oil pressure & water temperature) - Low water level alarm sender - Front radiator guard - Oil drain pump - Oil drain valve - Tools box

POWER GENERATION

PRIME POWER: The prime power is the maximum power available with varying loads for an unlimited number of hours. The average power output during a 24h period of operation must not exceed 80% of the declared prime power between the prescribed maintenance intervals and at standard environmental conditions. A 10% overload is permissible for 1 hour every 12 hours of operation.

STAND-BY POWER: The stand-by power is the maximum power available for a period of 500 hours/year with a mean load factor of 90% of the declared stand-by power. No kind of overloads is permissible for this use.

CONTINUOUS POWER: Contact the FPT sales organization.

LEGEND

Arrangement	Air Handling	Injection System
L (in line)	TCA (Turbocharged with aftercooler)	M (Mechanical)
V (90° "V" configuration)	TC (Turbocharged)	ECR (Electronic Common Rail)
	NA (Naturally Aspirated)	EUI (Electronic Unit Injector)
		MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

OT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTIC