On Road
Trucks
CURSOR 13

C13 ENT
420 kW (571 HP) @ 1900 rpm
Euro VI C

SPECIFICATIONS

Thermodynamic Cycle		Diesel 4 stroke
Air Handling		TCA
Bore x Stroke	millimeters	135 x 150
Total Displacement	liters	12.9
Valves per cylinder	number	4
Cooling System		liquid
Direction of Rotation	viewed facing flywheel	CCW
Compression ratio		16.5:1
Injection System		ECR
Arrangement		6L

PERFORMANCES

Peak power	kW (HP) @ rpm		420 (571) @ 1900
Peak torque	Nm (kgm) @ rpm		2500 (255) @ 1000
High idle speed	rpm		2320
Low idle speed	rpm		±530
Minimum starting temperature without auxiliaries		°C	-15°
Oil and oil filter maintenance interval for replacement		kilometer	-

STANDARD CONFIGURATION

Flywheel housing	type		SAE 1 - aluminium
Flywheel size	inch		17"
Intake manifold location			middle high / right side
Exhaust manifold location			middle high / left side / back
Turbocharger			lectronic Variable Geometry Turbocharger
Turbocharger location			Center / left side
Fan transmission ratio			1.3:1
Distance between fan - crankshaft centers		millimeters	X=-20 Y=225
Fuel filter		number	single cartridge - left side
Oil filter		number	single cartridge - right side
Oil sump			suspended sheet steel / front sump
Oil vapours blow-by circuit			close case ventilation
Oil heat exchanger			integrated into the block
Oil filler			on valve cover
Starter			24V - 5.5kW
Alternator			24 V - 90 A
Engine stop device			by electronic control unit
Wiring harness			interface wiring loom with accessories
Painting color			grey
Air compressor			0.352
Hydraulic steering pump		liters-minute	16 - 20 - 25
Maximum torque available from crankshaft pulley		newton-meter	800.000

WEIGHT AND DIMENSIONS

Dimensions	LxWxH (mm)	359 x 1034 x 1171
Dry Weight	Kg	1310

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



ON ROAD

IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

POWER & TORQUE



NOT INCLUDED IN STANDARD CONFIGURATION

Power Take Off (PTO)		-
PTO - transmission ratio		1.14:1
PTO - maximum available torque		800 Nm - -
Battery - minimum capacity recommended	Ah	473 Ah (24 V)
Battery - minimum cold cranking capacity recommended	Ah	24 V - 662 Ah

LEGEND

Arrangement
- L (in line)
- V (90° "V" configuration)

Air Handling
- TCA (Turbocharged with aftercooler)
- TC (Turbocharged)
- NA (Naturally Aspirated)

Turbocharger
- WG (Wastegate)
- VGT (Variable Geometry Turbocharger)
- TST (Twin Stage Turbocharge)

Injection System
- M (Mechanical)
- ECR (Electronic Common Rail)
- EUI (Electronic Unit Injector)
- MPI (Multi Point Injection)

Emission standard
- EEV (Enhanced Environmentally friendly Vehicle)

Exhaust System
- EGR (Exhaust Gas Recirculation)
- SCR (Selective Catalytic Reduction)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

AFTER TREATMENT SYSTEM

-

ON ROAD

LEGEND

Arrangement	Air Handling	Turbocharger	Injection System	Exhaust System
L (in line)	TCA (Turbocharged with aftercooler)	WG (Wastegate)	M (Mechanical)	EGR (Exhaust Gas Recirculation)
V (90° "V" configuration)	TC (Turbocharged)	VGT (Variable Geometry Turbocharger)	ECR (Electronic Common Rail)	SCR (Selective Catalytic Reduction)
	NA (Naturally Aspirated)		EUI (Electronic Unit Injector)	
		TST (Twin Stage Turbocharge)	MPI (Multi Point Injection)	

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE